

Main House Technical Specifications

Technicians

Technical Manager - Steve Payne

Senior Technician (Sound) - Drew White Senior Technician (Lighting) - Jonah Starkey

> Arena Theatre Wulfruna Street Wolverhampton WV1 1SE

Tel: 01902 322 507

Contact Details

Education & Outreach - 01902 322 646

Access and Inclusion - 01902 322 532

Technical Manager - Steve 01902 322 507

steve.payne@wlv.ac.uk

Senior Technician (Sound) - Drew 01902 322 616

drew.white@wlv.ac.uk

Senior Technician (Lighting) - Jonah 01902 322 487

<u>J.Starkey2@wlv.ac.uk</u>

Get In

The theatre Get In has ramped access direct to the stage area and is positioned at the far-left hand side of the executive staff car park. *Maximum width is 2.5 metres*.

Please note that the entrance to the executive staff car park has a height restricted entrance. *Maximum height is 3.2 metres. Maximum width is 3 metres.*

Dressing Rooms

Dressing room 1 - 6 persons

Dressing room 2 - 8 persons

Dressing room 3 - 15 persons

Dressing room 4 - 15 persons (Accessible)

Dressing room 5 - 6 persons (Accessible)

N.B. - If additional space is required, please contact the Technical Manager in advance.

Dressing Room Facilities

Security Dressing rooms are locked every evening and keys are available on request.

Wash Facilities All dressing rooms have hand basins and showers.

WC Facilities All dressing rooms have toilets.

Power All dressing rooms have 13amp power outlets.

Fittings All dressing rooms have mirrors with lighting surrounds, work surfaces,

chairs and costume rails (No rail in Dressing Room 2).

Communications All dressing rooms have show relay and paging.

Green Room Green room is situated FOH accessible, via pass door in main

dressing room corridor.

Wheelchair users Dressing rooms 4 and 5 are fully accessible via a lift.

Smoking No smoking is permitted anywhere on the premises which includes the

carpark with the exception of as part of a performance (agreed with technical

staff).

This includes E Cigarettes.

Personnel A Maximum of 50 persons allowed in the backstage area,

including venue staff, chaperones and performers.

Electrical Items Please ensure all electrical items used in the venue are P.A.T tested and show

a dated label.

Wi-fi Free Wi-fi is available, please ask at the box office.

Stage Dimensions

Setting Line	1300mm from Row A

Stage Width 9500mm
Stage Depth from Setting Line 8000mm
Grid Height 4670mm
Height under Stage Right Balcony 2200mm
Height under Stage Left Balcony 2200mm
Stage Right Wing Width 1270mm

Stage Left Wing Width 1900mm (upstage of prompt corner)

1520mm (downstage of prompt corner)

Up Stage Crossover 2900mm

Stage Equipment

12	12.5Kg Stage weights
8	Stage braces of varying lengths
1	12 rung Zarge
1	7 rung Zarge step ladders
1	5 rung Zarge step ladders
1	Genie GR-12 Runabout VPP (Licensed users only - category 3A)

Tabs and Cloths

White cyclorama (on tab track) Non-Removable.

Black tabs masking all wing entrances.

Black tabs to cover the white cyclorama.

Black half tabs with pulley operation stage right. 4160mm from the setting line.

Additional Stage Information

- a) Black wooden floor
- b) CCTV monitoring system with monitors located in control room, scene dock, all dressing rooms, green room and in the prompt desk stage left.
- c) Black dance floor is available upon request (dance companies only). 8000mm x 8000mm in 2000mm strips
- N.B. Due to the style and nature of the venue, screwing/ penetrating into the stage is not permitted. No set is to be placed on the in-house dance floor.

Lighting Equipment

Dimming and Control

02	ETC Sensor3 Digital Dimmer Racks
171	3Kw Dimmers
24	3Kw hard power terminating in 16a sockets at high level and 15a sockets at low level (2Kw)
01	ETC GiO (4096 outputs)
01	Monitor terminating in DVI-I (limited stock of additional monitors available on request)
01	Net 3, 4 port DMX gateway (permanent installation)

N.B. - Patched to 04 DMX Splitters, controlling up to 4 universes located in the control room. If you want to network any ETC devices, please address your IP range to: 10.101.100.XXX Subnet: 255.255.0.0

Lighting Equipment

Generic Fixtures

07	Strand quartet Fresnel	650w
10	Strand quartet PC	650w
13	Strand Cantata Fresnel	1200w
14	Strand Cantata PC	1200w
06	Source 4 15/30 zoom	750w
24	Source 4 25/50 zoom	750w
20	Source 4 Junior 25/50 zoom	575w
16	Parcan CP62	1000w
06	ADB ACP 1001 Cyc flood	1250w

Lighting Equipment

Intelligent Fixtures

02	ETC HES Lonestar
08	FTC HES SolaPix 19

Lighting Equipment

Houselights

GDS DMX controlled LED house lights, controllable in the following zones:

Address 1/500 Main Block
Address 1/501 Cross Aisle
Address 1/502 Rear Block
Address 1/503 House Left Balcony
Address 1/504 House Right Balcony

Address 1/505 Over Stage

Effects and Accessories

01 MDG ATMe

04 Doughty tank traps

01 14" Mirror Ball

01 Mirror Ball Rotator

01 Coda 1000w Cyc flood

01 63a 3ø (phase) rubber box with the following outputs:

16a 1ø (single phase) sockets
32a 1ø (single phase) sockets
32a 3ø (three phase) sockets

Additional Lighting Information

- a) The lighting desk (ETC GiO) can be replaced for an ETC ION (6144 outputs) upon request.
- b) Lighting control is located at the rear of the auditorium in the control room which has double glazed windows. It is shared with sound control. (This is not sound-proof).
- c) The Arena holds and extensive range of Lee lighting filters and Rosco R119 & R132 frost.
- d) One 63a 3ø (phase) socket located in the upstage cross over.
- e) The Arena carries a limited stock of Gobo's.
- f) The Arena holds size A & B Gobo holders for our Source 4 Zoom Profiles.
- q) The Arena holds a limited stock of M Gobo holders for our Source 4 Junior Zoom Profiles.

Lighting Bars and Rigging SWL/UDL

Bars A & D – K - 300Kg UDL (39Kg point load)

Bar M - 150Kg UDL (39Kg point load)

Bar C - 100Kg UDL (39Kg point load)

Each Unistrut is 120Kg UDL (80kg point load on any span)

There are also a number of rigging points (marked on plans) certified for increased point loads/performer flying. Please contact the technical manager for more information. Any performances wishing to utilize these rigging points must provide a detailed risk assessment for their use.

Boom Positions and UDL

- of fixed "prosc boom" position SL and SR, in line with Bar C, running from floor to 3615mm (with a section blocked by the balcony between 2345mm and 3170mm), 150Kg UDL (50Kg point load). Boom unit heights will be subject to adaptation.
- os fixed install mirrored boom positions SL and SR, in line with Bars E, G, and I, os arms per boom, 30Kg UDL (10Kg point load/per arm). These booms positions can be changed subject to discussion with the Arena technicians.

Sound Equipment

03 d&b E12-D (Permanent FOH Installation, Left, Right and Centre) 02 d&b E15-X Subs (Permanent FOH Installation) d&b E6 Delays (Permanent FOH Installation) 03 04 JBL 8320 (Permanent Side Surround Installation) 02 JBL 8320 (Permanent Rear Surround Installation) 05 d&b E8 05 d&b D6 Digital Amplifiers 02 Crown DSi1000 Amplifiers 01 Yamaha CL5 Digital Mixing Console 02 Ro8-D Digital Output Rack (Permanent Installation) 02 Ri8-D Input Rack (Permanent Installation) 01 Rio1608-D Digital Stage Box 01 Rio3224-D Digital Stage Box 02 Dante AVIO 2Ch Analog Output Adapter 01 Dante AVIO 2Ch Analog Input Adapter 04 Sennheiser EW-DX Transmitters and Receivers (utilizing site specific frequencies) Tall boom arm stands 80 07 Short boom arm stands 04 Straight stands 06 Table-top stands 04 Mackie SRM450 Active Speakers 01 8way Headphone Amp 01 8way DI Boxes 04 Single DI Boxes 01 Focusrite Scarlett 8i6 Microphones 07 Shure SM57 Microphone 06 Shure SM58 Microphone 01 Pulse PM580s Microphone 02 AKG C451b Microphone 03 AKG C1000 Microphone 01 AKG Groove Pack Perception Live Drum Mic Set: 01 AKG P2 03 AKG P4 02 AKG P17

E/V ND468 Microphone

04

Projector / A.V

- O1 Panasonic PT-RZ970 Laser Projector controllable by ArtNet (Permanent Installation)
- 01 Extensa Tab-tensioned Cinema-Grade Roller Screen (Permanent Installation)
- Oppo UDP-203 Ultra HD Blu-Ray Player (Permanent Installation)
- 01 Samsung QE65Q60AAUXXH 65" QLED 4K Smart TV
- 01 Datasat AP25 Audio Processor
- 01 Kramer VP-729 Scaler/Switcher
- 02 16" M1 Macbook Pro with QLab 4, Dante Virtual Soundcard and Dante Via

The projection system inputs on HDMI via Extron DTP Tx/Rx units. The system is capable of handling up to 7.1 surround sound with all processing taking place via the Datasat AP25. Inputs into the projection system are available in the following locations:

- Control room (next to sound desk)
- External Control Position (house left of auditorium)
- Downstage Left
- Downstage Right

Additional Sound Information

- a) Sound Control room is located at the rear of the auditorium. It has double glazed windows and is shared with lighting. One window in front of the sound control position can be opened.
- b) The Sound desk may be moved into the auditorium off to the far house left side.
- c) Monitor speakers are wired into a patchable speakon rack located in the control room.
- d) In-house Radio Microphones have both Handhelds and Lavalieres available. They are tuned to a venue specific licensed frequency. Please see below:
 - 526,200
 - 526.700
 - 527.350
 - 528.150
- e) A direct sound desk feed can be fed into either comms (to assist with hearing show content for cueing etc) or into the paging system to be then fed to the control room monitor speakers (in place of the standard show relay microphone) and dressing rooms, improving the clarity for shows with louder sound levels such as musicals and live music.

Live Stream Equipment

01	Blackmagic ATEM 4 M/E Broadcast Studio 4k
01	Blackmagic ATEM 1 M/E Advance Panel
01	Blackmagic Hyperdeck Studio Mini
01	Blackmagic Web Presenter 4K
01	Blackmagic Web Presenter HD
01	Blackmagic UltraStudio 4k Mini
01	Blackmagic Teranex Standards Converter
01	Blackmagic URSA Mini Pro 4.6k G2 (Fixed grid position)
03	E image EK650 Tripod with Fluid Head
01	Sigma 14-24mm f2.8 (On fixed camera in the grid)
02	Sigma 24-105mm f4
01	21" Apple iMac running macOS Catalina
01	22" 4K Multiview monitor
01	Blackmagic Teranex Mini HDMI to 12G SDI
01	Blackmagic Teranex Mini 12G SDI to HDMI
03	Blackmagic Micro Converter BiDirectional SDI/HDMI 3G
01	Blackmagic UltraStudio Recorder 3G
01	Blackmagic Mini Converter SDI Distribution 4K

Camera Patch point locations

01	Downstage Left
01	Downstage Right
01	Upstage Centre
01	Auditorium House Left (external sound position)
01	Auditorium House Right (House manager position)

N.B – All cameras use 2 SDI feeds in each position, 1 for signal and 1 to control the camera.

Additional Information

The Blackmagic system is 12G ready, capable of up to 2160p (4K) at 60fps. We have the capability to stream 2 feeds simultaneously (for instance a clean feed in 4K and a BSL feed in 1080p) as well as record at the same time, with access to 3 cameras to transition between.

If you are interested in using this equipment or have any technical queries, please contact the Technical Manager.

Accessibility

- Sennheiser mobile connect unit (compatible with any iOS or Smartphone)
 Audio Description workstation (Microphone, sound desk & dedicated show relay)
 Sennheiser infrared audio enhancing system (permanently installed to show relay)
 Sennheiser EZT 3011 Induction Neck Loop
 Sennheiser HDI 830 IR headphones
- N.B. If you require any further information on the Induction Loop or Audio Description please contact the Technical Manager.

10

Health and Safety

As part of our health and safety policy, an Arena Theatre technician will conduct a safety briefing with all staff working on the production before the Get In commences. The aim of the briefing is to introduce the key members of our technical staff, inform your staff of all evacuation procedures and draw their attention to any other possible hazards and policies that may be relevant to the production. This briefing is also an opportunity to introduce your staff to the house crew and discuss the schedule for the day.

A further briefing should take place with all members of the company on their arrival. This should take place in the auditorium and all technical work on stage should stop at this point for the briefing to take place.

Arena Theatre technical staff will provide information on in house Health & Safety Policies as required (Copies available on request). Arena Theatre Health & Safety Policies must be followed at all times. Special consideration must be given to Working at Height, Electrical Safety and Rigging/Suspended Equipment.

It is the responsibility of the visiting company to ensure all equipment and the items bought into The Arena are in a safe and suitable condition for use in a professional environment. This means all rigging equipment bought into the venue should have a SWL marked on it and all electrical equipment should hold a valid P.A.T Test. Any equipment that does not have the above may be deemed unsafe and may not be used.

Arena Theatre technicians have the final say over all matters relating to Health & Safety and have the right to refuse use of any equipment or other items they deem to be unsafe.